



Weltool

M3 Iron Arm Gooseneck Work Light



M3	
	329 lumens
	7.5 hours
	104m/ 341ft
	2700 candela

This is a user-friendly designed work light for maintenance or production environment. It doesn't need to connect the power cord. One big magnet on the base of M3 grabs onto steel surfaces even vertical adsorption for hands-free use, thus it can also help you to collect scattered nails, screws and other small parts. Silicone-wrapped metal gooseneck tube can be 360 degrees exposure in any direction. Light output is 329 lumens; 104m (341ft) beam distance; powered by 1/2/3 18650 Li-ion batteries, runs 7.5 hours without drop. No low frequency flashings. It can reach the same brightness no matter using one battery or two batteries. Even with one battery, M3 can still run 2.5 hours! When the battery power is low, it has a humanized flashing tips, leaving enough time for you to find batteries. At this time, even if you forget to replace the battery, M3 can automatically stop working in order to protect your battery from over discharge. "Iron arm" can be used for vehicle maintenance, producing machine tools, equipment inspection and other fields. Straighten the gooseneck M3 can be used as a flashlight as well.

"Iron arm" ----- your effective arm!

- Case Material : Anodized aerospace-grade aluminum construction
- Reflector System: Deep-dish parabolic smooth reflector
- Lamp Source: Features one powerful X-LED, 170LM/W peak beam intensity with a 50000 hours lifetime
- Light Output: 329 lumens; 2700 candela; 104m (341ft) beam distance; runs 7.5 hours
- (Using three Weltool INR18-26 rechargeable Li-ion battery tested)
- Battery: One or two or three rechargeable 18650 Li-ion batteries (Not included)
- ON/OFF: Push-button with a 50000 times lifespan
- One strong magnet embedded in the bottom of the cylinder body can be firmly attached to the metal surface
- Includes a battery holder which can install 3 18650 lithium-ion batteries
- Silicone-wrapped metal gooseneck, its diameter is 0.5 "(1.27cm)
- Lead-free PCB
- Fully regulated output for consistent lumen performance over the battery life
- A rope ring is on the body which can be inserted into by any lanyard its diameter is less than 5mm (0.019")
- Lower voltage hint function
- Over discharge protection
- No low frequency flashing, and no noise of current
- Non-slip knurled grip body
- Gold-coating phosphor bronze conductive spring
- 1m (39.37 ") impact resistance tested
- IP ratings up to IP66, can be used in heavy rain
- Individually serialized for positive identification.
- Dimensions: Face cap diameter 25.4mm (1"),
- Body Diameter 48mm (1.89"), Length 113mm(4.45"); head + gooseneck length 138mm(5.43") ±5mm (0.20")
- Weight: 350g(12.35 oz) (without battery)



Item Name	Part #
M3	71014
Accessory Name	Part #
INR18-26 18650 Li-ion Battery	71011
BC2 Battery Charger	71006